

SHEERWEAVE | 4650 3%



SPECIFICATION

WIDTHS 63" and 98"	BACTERIAL AND RESISTANCE	ASTM E 2180, ASTM G21, ASTM G22, AATCC30
ROLL LENGTH 30 Linear Yards	ACOUSTICAL	Part 3
FABRIC WEIGHT 13.30 oz/yd ²	PERFORMANCE	NRC 0.10 / SAA 0.11
FABRIC THICKNESS 0.026 in.	ENVIRONMENTAL	Certified to GREENGUARD and GREENGUARD
OPENNESS ~3%	BENEFITS	Gold
UV BLOCKAGE ~97%	FIRE CLASSIFICATION	California U.S. Title 19 (small scale), NFPA 701 TM#1 (small scale), NFPA 101 (Class A Rating), IBC Section 803.1.1 (Class A Rating), BS 5867 Part 2 Type B Performance, NFPA 701 TM#2 (large scale), CAN/ULC-S 109 (large and small scale)
COMPOSITION 17% Polyester, 83% Vinyl on Polyester		
WARRANTY 5-Years Interior, 10- Years Exterior		



Care & Handling

Remove dust with vacuum cleaner or compressed air. Do not scrub. Do not use solvents or any abrasive substance which might damage the coating of the fabric. Clean with a sponge or a soft brush dipped in soapy water using mild detergent. Rinse with clean water. Leave the blind down until completely dry. You can also very gently rub the fabric with a clean white pencil eraser to remove small stains.