




SHEERWEAVE | BASIC 3%



P02 WHITE



P04 WHITE/BONE



P05 WHITE/PLATINUM



V22 CHARCOAL/GRAY



V21 CHARCOAL

SPECIFICATION

WIDTHS 126"	FIRE CLASSIFICATION NFPA 701 TM#1 (small scale) TM#2 (large scale) NFPA 101 (Class A Rating) California U.S. Title 19 (small scale) BS 5867 Part 2 Type B Performance CAN/ULC-S 109 (large and small scale) CAN/CGSB2-4.162-M80 IBC Section 803.1.1 (Class A Rating)
ROLL LENGTH 30 Linear Yards	BACTERIA/ FUNGAL RESISTANCE ASTM E 2180 ASTM G21 AATCC30 Part 3 ASTM D 3273 ASTM G22 GREENGUARD Mold and Bacteria Standard ASTM 6329 includes Microban antimicrobial additives
FABRIC WEIGHT 16.4 oz/yd ²	LEAD FREE RoHS/Directive 2002/95/EC REACH (EC 1907/2006) compliant ANSI/WCMA A 100.1-2007 for lead content US Consumer Product Safety Commission Section 101
FABRIC THICKNESS 0.025 in.	WARRANTY 10-Year (Interior), 5-Year (Exterior)
OPENNESS ~3%	
UV BLOCKAGE ~97%	
COMPOSITION 38% Fiberglass, 62% Vinyl on Fiberglass	
ACCOUSTICAL VALUE NRC .60 / SAA .60	
PRINTABLE Yes	

